

Tubeless Snap-In Valves

Made with EDPM Rubber

65 psi maximum cold inflation pressure—
maximum rim thickness .156"



Part No.	Height	Valve Hole	Box Qty
TR413-50	1.25"	.453"	50
TR413-500	1.25"	.453"	500
TR414-50	1.50"	.453"	50
TR414-500	1.50"	.453"	500
TR418-50	2.00"	.453"	50
TR418-500	2.00"	.453"	500
TR423-50	2.50"	.453"	50

Tubeless Snap-In Valves with Chrome Sleeve & Cap

Made with EDPM Rubber

65 psi maximum cold inflation pres-
sure—maximum rim thickness .156"



Part No.	Height	Valve Hole	Box Qty
TR413C-50	1.25"	.453"	50
TR413C-500	1.25"	.453"	500
TR418C-50	2.00"	.453"	50
TR418C-500	2.00"	.453"	500

Tubeless Snap-In Valves

Made with EDPM Rubber

80 psi maximum cold inflation pressure—
maximum rim thickness .156"



Part No.	Height	Valve Hole	Box Qty
TR600HP-50	1.27"	.453"	50

Bolt-In Valves—Flush Mount

Torque at 25-45 in-lbs.



Part No.	Height	Valve Hole	Box Qty
TR416-50	1.44"	.453"/.625"	50
TR559-50	1.00"	.453"/.625"	50

Brass Truck Valves



Part No.	Specs.	Valve Hole	Box Qty
1) TR500T-10	Straight 2"	.625"	10
2) TR501T-10	Straight 1.5"	.625"	10
3) TR572T-10	Straight 3.75"	.625"	10
4) TR573	Straight	.625"	10
5) TR500A	23°	.625"	10
6) TR571E13-10	13°	.625"	10
7) TR572F-19-10	31°	.625"	10

Nickel Plated Brass Valves with O-rings



For aluminum wheels with 9.7mm/10mm (.382"-.394") valve hole and rim thickness of 5.5mm-8.4mm (.218"-.330" at valve hole.

8) TR543D-10	60°	9.7mm	10
9) TR544D-10	60°	9.7mm	10
10) TR545D-10	60°	9.7mm	10

Nickel Plated Brass Valves with Grommet



11) TR554D-10	60°	9.7mm	10
12) TR555D-10	60°	9.7mm	10