



# AIR OPERATED Oil & Grease DELIVERY SYSTEMS

OIL HANDLING

GREASE

Professional Quality. Complete Packages - includes all required equipment. Designed for 35 lb., 120 lb. and 400 lb. grease containers.

Includes - 50:1 high pressure pump, control handle, Z-swivel, drum cover, follower plate and 8' outlet hose.

MODEL NO.	DELIVERY CONTAINER	WEIGHT
JDL-5	35 LBS.	22 LBS.
JDL-16	120 LBS.	27 LBS.
JDL-16C	(SAME AS JDL-16 BUT INCLUDES CASTER BASE)	
JDL-55	400 LBS.	35 LBS.

#### SPECIFICATIONS:

PRESSURE RATIO	50:1
AIR INLET PRESSURE	70 - 115 PSI
AIR INLET CONNECTION	1/4" NPT (FEMALE)
AIR MOTOR EFFECTIVE DIAMETER	2.4" (63MM)
MAX PRESSURE	5600 PSI
OUTLET CONNECTION	1/4" NPT (MALE)



OIL

Complete Packages - includes all required equipment. For motor oil, synthetic oil, hydraulic oil and ATF. Designed for 16-gallon and 55-gallon drums.

Includes - 30:1 medium pressure pump, delivery gun, 10' delivery hose. 16-gallon package includes drum cover.

MODEL NO.	DELIVERY CONTAINER	WEIGHT
JDL-16	16-GAL	26 LBS.
JDL-55	55-GAL	22 LBS.

#### SPECIFICATIONS:

PRESSURE RATIO	3:1
AIR INLET PRESSURE	70 - 115 PSI
AIR INLET CONNECTION	1/4" NPT (FEMALE)
AIR MOTOR EFFECTIVE DIAMETER	2.49" (63MM)
MAX PRESSURE	348 PSI
OUTLET CONNECTION	1/2" NPT (MALE)

